# 30", 36", & 42" TPI Industrial Direct Drive Portable Blowers

**STANDARD** MODEL

> MARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.





#### **Features**

- Comes in sizes 30", 36", & 42"
- · Rocker switch
- · SJT type 3 conductor, 12' long cord
- Aluminum, 3 paddle blade
- Spiral, wire front and rear guards
- Corrosion and dent proof high density polyethylene housing
- 36" & 42" swivel model rotates 130° in 12 ½° increments and locks in place with a steel locking pin
- · Meets OSHA standards
- 1 Year limited warranty
- · Made in U.S.A.

## Motor Specifications

- · 120V, 1-Phase
- 36"-1/3HP 42"-1/2HP
- · Ball bearing
- · Permanent split capacitor
- 2-Speed on 36" model
- 1-Speed on 42" model
- · Permanently lubricated
- Totally enclosed

### Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	FAN		WHEEL	MOTOR	CFM* / RPM		VELOCITY PROFILE	AMPS	WT.	LIST
		SIZE	TYPE	SIZE HP	HIGH	LOW	CFM / Area Sq Ft	(HIGH)	(LBS.)	LIST	
08743902	PB 30-D	30"	STANDARD	1/4		4400	3800	7200 / 250	2.5	65	807
08744002	PBS 30-D	30"	SWIVEL			4400		7200 / 250		70	962
08730402	PB 36-D	36"	STANDARD	1/3		6500 / 1040	5400 / 950	11500 / 320	5.5	82	888
08730502	PBS 36-D	36"	SWIVEL			0500 / 1040	5400 / 950	11500 / 320		110	1209
08730702	PB 42-D	42"	STANDARD	10"	1/2	9,000 / 825		15000 / 240	6.0	102	1248
08730802	PBS 42-D	42"	SWIVEL	10"	1/2	9,000	/ 823	15000 / 340	6.0	128	1532

<sup>\*</sup>Measured 2 feet from face of fan

Note: Photograph is a representation of stocked models. Actual model may vary slightly in appearance

# 48" TPI Industrial Direct Drive Portable Blowers





⚠ WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### **Features**

- · Corrosion and dent proof high density polyethylene housing
- · Rocker switch
- SJT type 3 conductor, 12' long cord
- · Steel, 2 paddle blade
- · Spiral, wire front and rear guards
- · 10" wheels
- Swivel model rotates 130° in 12 ½° increments and locks in place with a steel locking pin
- Meets OSHA standards
- 1 Year limited warranty
- · Made in U.S.A.

### Motor Specifications

- 1-Phase
- 3/4 HP
- Ball bearing
- Permanent split capacitor
- 120V
- 1-Speed
- · Permanently lubricated
- · Totally enclosed

### **Features**

CATALOG MO	MFG MODEL	SIZE	FAN TYPE	MOTOR HP	CFM* / RPM	VELOCITY PROFILE	AMPS	DIMENSIONS			WT.	LIST
	NUMBER					CFM / Area Sq Ft	(HIGH)	"H"	"D"	"W"	(LBS)	LIST
07997802	PB 48-D-OP	48"	STANDARD	3/4	11,800 / 825	14000 / 360	10.3	58.5	29	55.5	117	1802
07998002	PBS 48-D-OP	48"	SWIVEL	3/4	11,800 / 825	14000 / 360	10.3				142	2057