ALUMINUM LITE LOAD LIFT- ALLW-2420-4SFL

APPROX WEIGHT: 126.04 lbs.

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 33 1/8" 3D VIEW **SCALE 1:16** 24" 69 5/16" Ø8" 60" RAISED 6 1/8" LOWERED DIMENSION TOLERANCE ± 1/4" I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION Ρ COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.

UNITS REQUIRING APPROVAL DRAWINGS OR Ρ 27 3/16 R 0 STANDARD FEATURES MODIFIED ARE NON-RETURNABLE ٧ MODEL NUMBER: ALLW-2420-4SFL SPECIAL FEATURES [] As drawn [] As marked Α CAPACITY: 400 LBS. NONE Signed: Date: PLATFORM WIDTH: 24" PLATFORM LENGTH: 20" **Printed Name:** OVERALL WIDTH: 27 3/16" LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING **OVERALL LENGTH: 33 1/8"** DISTRIBUTOR'S NAME: **OVERALL HEIGHT: 69 5/16"** VESTIL MANUFACTURING RAISED HEIGHT: 60" W.O.# DRAWN BY: KY LOWERED HEIGHT: 6 1/8" DATE: 8/30/05 SALES: X HAND WINCH OPERATION reference: X SCALE: 1:14 FILE NAME: INCLUDES FLOOR LOCK **ALUMINUM CONSTRUCTION**

Quoted lead time: $_{
m Y}$

QUOTE #

Χ

42-007-019