

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

SHALLOW DEPTH WORKTOP REFRIGERATOR

WTR27HC Solid Door With Flat Top Hydrocarbon Series

MODEL: WTR27HC-FLT



*Note: Shown with optional full electronic control

7 Year Compressor Warranty

7 Year Parts/Labor Warranty

- Stainless steel front, sides, door and grille (galvanized back & bottom)

CABINET CONSTRUCTION

- Interior liner is made of corrosion resistant aluminum
- Stainless steel top for added durability
- Flat top
- Mechanical control
- Interior thermometer is standard
- Self-closing door with 120° stay-open feature, on lift-off hinges
- Magnetic gasket attached to each door for positive seal
- 6" Casters, two (2) with brakes standard
- Two (2) epoxy-coated steel wire shelves
- Field-reversible door (hinge kit not included)

OPTIONS & ACCESSORIES

- Stainless steel back
- Stainless steel interior
- 16 Gauge stainless steel top
- Full electronic control*
- Additional shelves
- Shelf clips
- Glass door option
- Right or left hinged door
- Locks (solid doors only)
- Wire shelf divider
- Cutting board
- 3" Casters
- 6" Legs (stainless steel, black or seismic/flange)
- Low profile casters
- Roller kit
- Remote option** (see note on back on page)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil
- Refrigerators capable of maintaining product temperature between 36°F and 38°F












MODEL	WTR27HC-FLT	
EXTERNAL DIMENSIONAL DATA		
Width Overall	27"	
Depth Overall with Handle & Bumper	30"	
Height Overall with 6" Casters	35 ½"	
Number of Doors	1	
Depth with Door Open 90°	53 1⁄4"	
Door Opening	22 %" x 21 %"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	5.25	
Internal Width Overall (in)	23"	
Internal Depth Overall (in)	18"	
Internal Height Overall (in)	23"	
Number of Shelves	2	
ELECTRICAL DATA		
Full Load Amperes	2.0	
Voltage	115/60/1	
Nema Plug (8' cord)	5-15P	
REFRIGERATION DATA		
Horsepower	1/6	
Capacity (BTU/Hr)	1110	
Heat Rejection (BTU/Hr)	1665	
Charge (lbs/grams/ounces)	0.1323 / 60 / 2.12	
SHIPPING DATA		
Gross Weight - Crated	161 lbs	
Height - Crated	35"	
Width - Crated	23"	
Depth - Crated	26"	

^{**}NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

Worktop Refrigerator - Shallow Depth Model: WTR27HC-FLT





ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord and plug set.

